


Item: LED pendant light
Mounting: suspended
Housing: aluminum
Finish options:
 01-white matte
 11-black matte
 20-golden matte

LED: CREE/Citizen
Volt AC: 220-240V
Frequency: 50/60Hz
CCT: 2700K-3000K-4000K
LED driver options:
 ND - non-dimmable
 PH - phase dimmable
 010V - 0-10V dimmable
 DALI - compatible

Notes:
 * other RAL color available on request
 * other dimensions available on request
 * Lumen output data is based on 3000K



| Ref code: | Watt | Lm(±) | DiaxH1xH2(mm) |
|-----------------------|------|-------|---------------|
| 55.53.01.05.003.01.05 | 5W | 400 | 50x400x1940 |
| 55.53.01.05.003.02.07 | 7W | 560 | 50x700x2240 |
| 55.53.01.05.004.01.05 | 5W | 400 | 50x400x1940 |
| 55.53.01.05.004.02.07 | 7W | 560 | 50x700x2240 |
| 55.53.01.05.005.01.10 | 10W | 900 | 66x400x1960 |
| 55.53.01.05.005.02.15 | 15W | 1350 | 66x700x2260 |



Beam Angle-Code:
 10°-BA10
 15°-BA15
 26°-BA26
 35°-BA35
 47°-BA47

