

mirror lights

Mounting: wall surface mounted

Housing: stainless steel

Diffuser: PMMA

Finish options:

16-polished chrome

18-satin chrome

*other colors are available on request

LED: SMD 2835

CRI: >80

AC Volt: 220-240V

Frequency: 50/60Hz

Color temperature, K:

CT30-3000k

CT40-4000k

Notes: *Lm given in data is based on 3000k and is delivered

*other CCT is available on request

LED driver options:

ND - non-dimmable

PH - phase dimmable

010V - 0-10V dimmable


DALI - compatible

Application: indoors:


hotels, residential

private, public

bathroom, next to mirrors



Ref Code	Watt	Lm(±)	L
13.29.099.01.09	9W	540	420
13.29.100.01.12	12W	720	520
13.29.101.01.14	14W	840	620
13.29.102.01.16	16W	960	720
13.29.103.01.18	18W	1080	800
13.29.104.01.24	24W	1440	1120



Ref Code	Watt	Lm(±)	L
13.29.105.01.09	9W	540	420
13.29.106.01.12	12W	720	520
13.29.107.01.14	14W	840	620
13.29.108.01.16	16W	960	720
13.29.109.01.18	18W	1080	800
13.29.110.01.24	24W	1440	1120

